

MINIMUM 500 UNITS



Model No:

Features:

- 1) Dimensions: 92 x 92 x 25mm
- 2) Voltage: 12V, 24V, 48V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)
- 5) High efficiency and low noise
- 6) Large volume flow and long life expectancy



Model No.:

- 1) Dimensions: 60 x 60 x 10mm, 60 x 60 x 15mm
- 2) Voltage: 5V, 12V, 24V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)
- 5) High efficiency and low noise
- 6) Large volume flow and long life expectancy



Model No:

- 1) Dimensions: 50 x 50 x 10mm, 50 x 50 x 15mm
- 2) Voltage: 5V, 12V, 24V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)
- 5) High efficiency and low noise
- 6) Large volume flow and long life expectancy



Model No:

- 1) Dimensions: 70 x 70 x 15mm
- 2) Voltage: 12V, 24V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)
- 5) High efficiency and low noise
- 6) Large volume flow and long life expectancy



Model No:

- 1) Dimensions: 70 x 70 x 25mm
- 2) Voltage: 12V, 24V, 48V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)



Model No:

- 1) Dimensions: 80 x 80 x 20mm
- 2) Voltage: 12V, 24V, 48V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)



Model No:

- 1) Dimensions: 80 x 80 x 25mm
- 2) Voltage: 12V, 24V, 48V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)



Model No:

- 1) Dimensions: 80 x 80 x 15mm
- 2) Voltage: 5V, 12V, 24V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)



Model No:

- 1) Dimensions: 120 x 120 x 25mm, 120 x 120 x 38mm
- 2) Voltage: 12V, 24V, 48V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)



Model No:

- 1) Dimensions: 200 x 200 x 60mm
- 2) Voltage: 12V, 24V, 48V
- 3) Bearing: ball bearing
- 4) High efficiency and low noise



Model No:

- 1) Dimensions: 40 x 40 x 10mm, 40 x 40 x 20mm
- 2) Voltage: 5V, 12V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)



Model No:

- 1) Dimensions: 50 x 50 x 10mm, 50 x 50 x 15mm
- 2) Voltage: 5V, 12V, 24V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)



Model No:

- 1) Dimensions: 30 x 30 x 7mm, 30 x 30 x 10mm
- 2) Voltage: 5V, 12V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)



Model No:

- 1) Dimensions: 172 x 150 x 51mm
- 2) Voltage: 12V, 24V, 48V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)



DC Blower Fan
Model No:

- 1) Dimensions: 97 x 97 x 33mm
- 2) Voltage: 12V, 24V
- 3) Bearing: ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)
- 5) High efficiency and low noise
- 6) Large volume flow and long life expectancy



DC Blower Fan
Model No:

- 1) Dimensions: 50 x 50 x 15mm, 75 x 75 x 30mm
- 2) Voltage: 12V, 24V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)
- 5) High efficiency and low noise
- 6) Large volume flow and long life expectancy



DC Blower Fan
Model No:

- 1) Dimensions: 120 x 120 x 32mm
- 2) Voltage: 12V, 24V
- 3) Bearing: ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)



DC Centrifugal Fan

Voltage: 12V, 24V, 48V

RM ELECTRONICS DISTRIBUTOR
3298 NW 47th AVE
Coconut Creek, FL 33063
954-261-3433
954-861-2925
www.rmelectronic distributor.com



AC Axial Fan
Model No:

- 1) Dimensions: 80 x 80 x 25mm, 80 x 80 x 38mm, 92 x 92 x 25mm, 92 x 92 x 38mm, 110 x 110 x 25mm, 120 x 120 x 25mm, 120 x 120 x 38mm, 172 x 150 x 38mm, 172 x 150 x 51mm, 160 x 160 x 62mm, 180 x 180 x 65mm, 200 x 200 x 60mm, 220 x 220 x 60mm, 250 x 250 x 90mm, 125 x 125 x 38mm
- 2) Voltage: 110V, 220V
- 3) Bearing: sleeve bearing and ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)



DC Cross-Flow Fan
Model No:

- 1) Dimensions: 30 x 30 x 150mm, 30 x 30 x 290mm
- 2) Voltage: 12V, 24V
- 3) Bearing: ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)
- 5) High efficiency and low noise
- 6) Large volume flow and long life expectancy

DC Cross-Flow Fan
Model No:

- 1) Dimensions: 30 x 30 x 90mm
- 2) Voltage: 12V, 24V
- 3) Bearing: ball bearing
- 4) Impeller and frame: plastic (UL 94V-0)
- 5) High efficiency and low noise
- 6) Large volume flow and long life expectancy



Fan Guard

Dimensions: YM-03 for 30mm fan, YM-04 for 40mm fan, YM-05 for 50mm fan, YM-06 for 60mm fan, YM-07 for 70mm fan, YM-08 for 80mm fan, YM09 for 92mm fan, YM-12 for 120mm fan, YM-15 for 150mm fan